



## SAE-560-A

Addressable sounder

### Description

SAE-560-A acoustic addressable sounder from Easy-Detect, with very low consumption. It has a maximum power of 110 dB.

It has 32 tones and 3 volume levels, high, medium and low, which are selected through the central configuration. It is compatible with all Easy-Detect addressable fire alarm control panels.

Addressing of this range can be done:

- Using PGE-100 manual programming tool.
- By serial number of the devices
- By app via Bluetooth
- Through self-programming

### Applications

The easy-detect SAE-560-A sounder is designed to warn people to evacuate in the event of a fire.

### Features

Built-in docking station.

### Technical Features

<b>SOUNDER</b>	Loop Features:	Occupies 1 address in the loop
	Working voltage:	38 VDC
	Consumption in rest:	< 120 µA
	Consumption in alarm:	< 6 mA

<b>CONNECTION</b>	2 x 1,5 mm <sup>2</sup> braided and shielded connection.
-------------------	--

<b>ENVIRONMENT</b>	Working temperature:	From -10°C to 70°C
	Relative humidity:	95% without condensation.
	IP Index:	IP30

<b>PHYSICAL FEATURES</b>	Dimensions:	109 x 82,5 mm
	Material:	ABS

### CERTIFICATION

EN  
54-3

### Dimensions

