



SAE-560-AI

Addressable sounder
with built-in isolator

Description

SAE-560-AI acoustic addressable sounder from Easy-Detect, with very low consumption short-circuit isolator. It has a maximum power of 110 dB.

It has 32 tones and 3 volume levels, high, medium and low, which are selected through the central configuration. It is compatible with all Easy-Detect addressable fire alarm control panels.

Addressing of this range can be done:

- Using PGE-100 manual programming tool.
- By app via Bluetooth
- By serial number of the devices
- Through self-programming

Applications

The easy-detect SAE-560-AI sounder is designed to warn people to evacuate in the event of a fire.

Features

Built-in docking station.

Technical Features

| | | |
|----------------|-----------------------|--------------------------------|
| SOUNDER | Loop Features: | Occupies 1 address in the loop |
| | Working voltage: | From 31 to 40 VDC |
| | Consumption in rest: | < 300 μ A |
| | Consumption in alarm: | < 10 mA |

| | |
|-------------------|--|
| CONNECTION | 2 x 1,5 mm ² braided and shielded connection. |
|-------------------|--|

| | | |
|--------------------|----------------------|---------------------------|
| ENVIRONMENT | Working temperature: | From -10°C to 40°C |
| | Relative humidity: | 95% without condensation. |
| | IP Index: | IP30 |

| | | |
|--------------------------|-------------|---------------|
| PHYSICAL FEATURES | Dimensions: | 109 x 82,5 mm |
| | Material: | ABS |

CERTIFICATION

EN
54-3

EN
54-17

Dimensions

