



**The image does not correspond to the model*

MAE-511

1 relay output addressable module

Description

1 relay output addressable module MAE-511, provides a C, NO, NC contact. With communication protocol AF Ultrafast. Direct power supply from the loop occupying one address per output. Reduced box with LED status indicator with 180° visualization. Individual removable strips. Installation on DIN or flat rail with the possibility of incorporating an ONE-BOX box or SIX- BOX. Black and white.

Addressing of this range can be done:

- Using PGE-100 manual programming tool
- By app via Bluetooth
- By serial number of the devices
- Through self-programming

Applications

They are ideal for activating or deactivating external devices using a NC or NA dry contact such as; gates, elevators, air conditioning systems.

Features

- Made in Spain
- LED status indicator 180°
- Removable terminal block
- Protection box
- CPR EN54-18 / EN54-17 certified
- Rail Din

Technical Features

DETECTOR	Working voltage:	From 31 to 40 VDC	Relai Contact:	1 A @ 30VDC
Loop Features	Consumption in rest:	< 300 µA		
	Consumption in alarm:	< 3 mA		
CONNECTION	2 x 1,5 mm ² braided and shielded			
ENVIRONMENT	Working temperature:	From -10°C to 40°C		
	Relative humidity:	95% without condensation.		
	IP Index:	IP40		
PHYSICAL FEATURES	Head (height x diameter):	92 x 105 x 22 mm		
	Material:	ABS		
CERTIFICATION	<div>EN 54-18</div>			

Dimensions

